





TESTING TEMPERATURE: 20°C TESTING HUMIDITY: 50%

Electronics: BYHX

MODEL、HEAD LAYOUT、 SETTING	PASS	FEATHER TYPE		FEATHER	TESTING SQM <sup>2</sup>	TAKE TIME MIN / SEC		PRINTING SPEED SQM <sup>2/H</sup>	UV LED LAMP	
		Feather Type	Gradient			Feather	0%			
<h3>H3000M</h3>  <p>Kyocera 6c Grating resolution: 25400 resolution; 604 fire frequency: 27K high speed bi-direction</p>	8PASS	GRADIENT	WEAK	3.0143	7	12	25.1190	LED 300		
			MIDDLE	3.0143	9	22	19.3086			
			STRONG	3.0143	10	48	16.7460			
		Uniform	WEAK	3.0143	13	11	13.7186			
			MIDDLE	3.0143	14	11	12.7514			
			STRONG	3.0143	16	14	11.1411			
	6PASS	GRADIENT	WEAK	3.0067	5	26	33.2024			
			MIDDLE	3.0067	6	41	26.9925			
			STRONG	3.0067	8	8	22.1803			
		Uniform	WEAK	3.0067	9	28	19.0563			
			MIDDLE	3.0067	10	45	16.7814			
			STRONG	3.0067	12	15	14.7265			
	4PASS	GRADIENT	WEAK	3.0143	3	45	48.2285			
			MIDDLE	3.0143	4	38	39.0338			
			STRONG	3.0143	5	26	33.2865			
		Uniform	WEAK	3.0143	6	5	29.7299			
			MIDDLE	3.0143	7	26	24.3305			
			STRONG	3.0143	8	7	22.2822			
	<h3>H3000M</h3>  <p>Kyocera 6c+w Grating resolution: 25400 resolution; 604 fire frequency: 27K high speed bi-direction</p>	8PASS	GRADIENT	WEAK	3.0143	8			22.6071	LED 300
				MIDDLE	3.0143	10	12		17.7311	
				STRONG	3.0143	12	12		14.8243	
			Uniform	WEAK	3.0143	13	31		13.3803	
				MIDDLE	3.0143	13	31		13.3803	
				STRONG	3.0143	16	27		10.9943	
6PASS		GRADIENT	WEAK	3.0067	6	31	27.6828			
			MIDDLE	3.0067	7	54	22.8354			
			STRONG	3.0067	9	37	18.7591			
		Uniform	WEAK	3.0067	11	3	16.3258			
			MIDDLE	3.0067	12	25	14.5288			
			STRONG	3.0067	14	3	12.8398			
4PASS		GRADIENT	WEAK	3.0143	4	14	42.7221			
			MIDDLE	3.0143	5	22	33.7000			
			STRONG	3.0143	6	7	29.5679			
		Uniform	WEAK	3.0143	6	44	26.8599			
			MIDDLE	3.0143	8	16	21.8778			
			STRONG	3.0143	9	0	20.0952			
<h3>H3000M</h3>  <p>KYOCERA 6C 2row grating resolution 25400 resolution 604 high speed bi-direction</p>		8PASS	GRADIENT	WEAK	3.2000	4	30	44	LED 300	
				MIDDLE	3.2000	5	25	36		
				STRONG	3.2000	6	25	31		
			Uniform	WEAK	3.2000	7	14	28		
				MIDDLE	3.2000	7	14	28		
				STRONG	3.2000	8	39	23		
	6PASS	GRADIENT	WEAK	3.2000	3	32	55			
			MIDDLE	3.2000	4	12	47			
			STRONG	3.2000	4	56	40			
		Uniform	WEAK	3.2000	5	40	35			
			MIDDLE	3.2000	5	40	35			
			STRONG	3.2000	7	8	28			
	4PASS	GRADIENT	WEAK	3.2000	2	34	76			
			MIDDLE	3.2000	3	2	64			
			STRONG	3.2000	3	30	56			
		Uniform	WEAK	3.2000	4	42	42			
			MIDDLE	3.2000	4	42	42			
			STRONG	3.2000	6	10	32			


# H3000M



KYOCERA 6C 2row+2w  
grating resolution 25400  
resolution 604  
high speed bi-direction color  
+white+color printing mode

8PASS	GRADIENT	WEAK	3.2000	12	34	16	LED 300
		MIDDLE	3.2000	15	36	13	
		STRONG	3.2000	18	40	11	
	Uniform	WEAK	3.2000	26	13	8	
		MIDDLE	3.2000	29	25	8	
		STRONG	3.2000	32	53	7	
6PASS	GRADIENT	WEAK	3.2000	9	26	21	
		MIDDLE	3.2000	11	41	17	
		STRONG	3.2000	14	7	15	
	Uniform	WEAK	3.2000	18	55	11	
		MIDDLE	3.2000	21	15	10	
		STRONG	3.2000	24	52	9	
4PASS	GRADIENT	WEAK	3.2000	8	13	24	
		MIDDLE	3.2000	8	56	22	
		STRONG	3.2000	9	35	21	
	Uniform	WEAK	3.2000	12	55	16	
		MIDDLE	3.2000	14	7	15	
		STRONG	3.2000	16	35	13	

# H1600M




KYOCERA 6C+W  
150DPI  
resolution: 600  
fire frequency: 27K  
high speed bi-direction

8PASS	GRADIENT	WEAK	2.4000	6	35	21.8734	LED 300
		MIDDLE	2.4000	8	11	17.5967	
		STRONG	2.4000	9	48	14.6939	
	Uniform	WEAK	2.4000	12	7	11.8845	
		MIDDLE	2.4000	13		11.0769	
		STRONG	2.4000	14	36	9.8630	
6PASS	GRADIENT	WEAK	2.4000	5	6	28.2353	
		MIDDLE	2.4000	6	11	23.2884	
		STRONG	2.4000	7	22	19.5475	
	Uniform	WEAK	2.4000	8	36	16.7442	
		MIDDLE	2.4000	9	49	14.6689	
		STRONG	2.4000	11	2	13.0514	
4PASS	GRADIENT	WEAK	2.4000	3	35	40.1860	
		MIDDLE	2.4000	4	19	33.3591	
		STRONG	2.4000	5	5	28.3279	
	Uniform	WEAK	2.4000	5	40	25.4118	
		MIDDLE	2.4000	6	48	21.1765	
		STRONG	2.4000	7	23	19.5034	

MODEL、HEAD LAYOUT、SETTING	PASS	FEATHER TYPE	FEATHER	TESTING SQM <sup>2</sup>	TAKE TIME	PRINTING SPEED SQM <sup>2H</sup>	UV LED LAMP
---------------------------	------	--------------	---------	--------------------------	-----------	----------------------------------	-------------


# H1600M



KYOCERA 6C  
150DPI  
resolution: 600  
fire frequency: 27K  
high speed bi-direction

8PASS	GRADIENT	WEAK	2.4000	5	55	24.3380	LED 300
		MIDDLE	2.4000	7	21	19.5918	
		STRONG	2.4000	8	51	16.2712	
	Uniform	WEAK	2.4000	10	41	13.4789	
		MIDDLE	2.4000	11	40	12.3429	
		STRONG	2.4000	13	36	10.5882	
6PASS	GRADIENT	WEAK	2.4000	4	35	31.4182	
		MIDDLE	2.4000	5	34	25.8683	
		STRONG	2.4000	6	38	21.7085	
	Uniform	WEAK	2.4000	7	43	18.6609	
		MIDDLE	2.4000	8	50	16.3019	
		STRONG	2.4000	9	57	14.4724	
4PASS	GRADIENT	WEAK	2.4000	3	12	45.0000	
		MIDDLE	2.4000	3	53	37.0815	
		STRONG	2.4000	4	34	31.5328	
	Uniform	WEAK	2.4000	5	5	28.3279	
		MIDDLE	2.4000	6	8	23.4783	
		STRONG	2.4000	6	40	21.6000	

# H1600M



KYOCERA 6C two row  
150DPI  
resolution: 600  
fire frequency: 27K  
high speed bi-direction

8PASS	GRADIENT	WEAK	2.4000	5	55	25	LED 300
		MIDDLE	2.4000	7	21	21	
		STRONG	2.4000	8	51	17	
	Uniform	WEAK	2.4000	10	41	14	
		MIDDLE	2.4000	11	40	13	
		STRONG	2.4000	13	36	12	
6PASS	GRADIENT	WEAK	2.4000	4	35	32	
		MIDDLE	2.4000	5	34	27	
		STRONG	2.4000	6	38	23	
	Uniform	WEAK	2.4000	7	43	20	
		MIDDLE	2.4000	8	50	17	
		STRONG	2.4000	9	57	15	
4PASS	GRADIENT	WEAK	2.4000	3	12	46	
		MIDDLE	2.4000	3	53	38	
		STRONG	2.4000	4	34	33	
	Uniform	WEAK	2.4000	5	5	29	
		MIDDLE	2.4000	6	8	24	
		STRONG	2.4000	6	40	23	